ADA Accessibility Guidelines for Recreation Facilities

Recreation Homepage | ADAAG Homepage

Published in the *Federal Register* on September 3, 2002. PDF version

36 CFR Part 1191 [Docket No. 98-5] RIN 3014-AA16

NOTE: These guidelines have not been incorporated in the Department of Justice accessibility standards and are, therefore, not enforceable.

- Summary
- Background
- General Issues
- Section-by-Section Analysis
- Regulatory Process Matters
- Text of the Guidelines
- Appendix

AGENCY: Architectural and Transportation Barriers Compliance Board.

ACTION: Final rule.

SUMMARY: The Architectural and Transportation Barriers Compliance Board (Access Board) is issuing final accessibility guidelines to serve as the basis for standards to be adopted by the Department of Justice for new construction and alterations of recreation facilities covered by the Americans with Disabilities Act (ADA). The guidelines include scoping and technical provisions for amusement rides, boating facilities, fishing piers and platforms, golf courses, miniature golf, sports facilities, and swimming pools and spas. The guidelines will ensure that newly constructed and altered recreation facilities meet the requirements of the ADA and are readily accessible to and usable by individuals with disabilities.

DATES: The guidelines are effective October 3, 2002. The incorporation by reference of certain publications listed in the guidelines is approved by the Director of the Federal Register as of October 3, 2002.

Appendix A to Part 1191 — Americans With Disabilities Act (ADA) Accessibility Guidelines for Buildings and Facilities

* * * * * *

3.5 Definitions.

* * * * *

* * * * *

Golf Car Passage. A continuous passage on which a motorized golf car can operate.

Teeing Ground. In golf, the starting place for the hole to be played.

* * * * *

15* RECREATION FACILITIES.

Newly designed or newly constructed and altered recreation facilities shall comply with the applicable requirements of section 4 and the special application sections, except as modified or otherwise provided in this section.

* * * * * *

15.4 Golf.

15.4.1 General. Newly designed or newly constructed and altered golf courses, driving ranges, practice putting greens, and practice teeing grounds shall comply with 15.4.

15.4.2* Accessible Route - Golf Course. An accessible route shall connect accessible elements and spaces within the boundary of the golf course. In addition, an accessible route shall connect the golf car rental area, bag drop areas, practice putting greens, accessible practice teeing grounds, course toilet rooms, and course weather shelters. The accessible route required by this section shall be 48 inches (1220 mm) minimum wide. Where handrails are provided, the accessible route shall be 60 inches (1525 mm) minimum wide.

Exception 1: A golf car passage complying with 15.4.7 shall be permitted in lieu of all or part of an accessible route required by 15.4.2.

Exception 2: The handrail requirements of 4.8.5 shall not apply to an accessible route located within the boundary of a golf course.

15.4.3* Accessible Route - Driving Ranges. An accessible route shall connect accessible teeing stations at driving ranges with accessible parking spaces and shall be 48 inches (1220 mm) wide minimum. Where handrails are provided, the accessible route shall be 60 inches (1525 mm) wide minimum.

Exception: A golf car passage complying with 15.4.7 shall be permitted in lieu of all or part of an accessible route required by 15.4.3.

- 15.4.4 Teeing Grounds. Teeing grounds shall comply with 15.4.4.
- 15.4.4.1 Number Required. Where one or two teeing grounds are provided for a hole, at least one teeing ground serving the hole shall comply with 15.4.4.3. Where three or more teeing grounds are provided for a hole, at least two teeing grounds shall comply with 15.4.4.3.
- 15.4.4.2 Forward Teeing Ground. The forward teeing ground shall be accessible.

Exception: In alterations, the forward teeing ground shall not be required to be accessible where compliance is not feasible due to terrain.

- 15.4.4.3 Teeing Grounds. Teeing grounds required by 15.4.4.1 and 15.4.4.2 shall be designed and constructed so that a golf car can enter and exit the teeing ground.
- 15.4.5 Teeing Stations at Driving Ranges and Practice Teeing Grounds. Where teeing stations or practice teeing grounds are provided, at least 5 percent of the practice teeing stations or practice teeing grounds, but not less than one, shall comply with 15.4.4.3.
- 15.4.6 Weather Shelters. Where weather shelters are provided on a golf course, each weather shelter shall have a clear floor or ground space 60 inches (1525 mm) minimum by 96 inches (2440 mm) minimum and shall be designed and constructed so that a golf car can enter and exit.
- 15.4.7 Golf Car Passage. Where curbs or other constructed barriers are provided along a golf car passage to prohibit golf cars from entering a fairway, openings at least 60 inches (1525 mm) wide shall be provided at intervals not to exceed 75 yds (69 m).
- 15.4.7.1 Width. The golf car passage shall be 48 inches (1220 mm) minimum wide.
- 15.4.8 Putting Greens. Each putting green shall be designed and constructed so that a golf car can enter and exit the putting green.
